ZEUS 100 MINI

COMPACT 2X50W RMS BLUETOOTH CLASS-D AMPLIFIER

The Zeus 100 Mini is a ultra-compact, high-efficiency Class-D stereo amplifier engineered specifically for discreet, fixed-architecture installations. Housed in a rugged, heat-dissipating aluminum chassis, it is designed for seamless in-wall or concealed mounting behind panels, furniture, or inside architectural enclosures.

Delivering 2 x 50W RMS of crisp, dynamics-driven audio into a 4-ohm load, the Zeus 100 Mini combines modern wireless performance via Bluetooth 5.3 with dependable wired connectivity through standard Euroblock (Phoenix) terminals and an auxiliary 3.5mm line input.

Whether powering multi-room residential background music, commercial storefront sound, or sleek hospitality audio systems, the Zeus 100 Mini provides high-fidelity performance with minimal visual and physical footprint.

ZEUS 100 MINI

Zeus-100-Mini-Front_tn.jpg



Zeus-100-Mini-Rear_tn.jpg

Class-D No Fan Low Impedance Bluetooth

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

ZEUS 100 MINI

COMPACT 2X50W RMS BLUETOOTH CLASS-D AMPLIFIER

PRODUCT DETAILS

KEY FEATURES

Compact Aluminum Housing: Heavy-duty, passive-cooling aluminum enclosure crafted for in-wall, recessed, or concealed installations where space is at a premium.

High-Efficiency Class-D Power: Delivers robust 2 x 50W RMS output with exceptionally low heat generation and maximum energy efficiency.

Seamless Bluetooth 5.3 Connectivity: Features the latest Bluetooth standard for fast, stable, and extended-range wireless streaming from smartphones, tablets, and media devices.

Flexible Audio Connectivity: Includes a standard 3.5mm auxiliary line input alongside secure screw terminal connections (Euroblock) for streamlined wiring.

Low Impedance Drive: Capable of driving loads down to 4 Ohms per output, ensuring compatible integration with a wide variety of architectural and surface-mount loudspeakers.

SPECIFICATIONS

Power Supply	AC 230V-50Hz screw terminals (Euroblock)
Amplifier Construction	Class D
Output Power (RMS @ 4?)	2 x 50W
Minimum Impedance	4? per output
Frequency Response	10Hz - 16kHz (-3dB)
Bluetooth Version	5.3
Auxiliary Input	L/G/R Line (3.5mm)
Input Impedance	10k Ohms (Line)
Input Sensitivity	0dB (Line)

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

ZEUS 100 MINI

COMPACT 2X50W RMS BLUETOOTH CLASS-D AMPLIFIER

Speaker Outputs	L-/L+/R-/R+ screw terminals (Euroblock)
Dimensions (WxDxH)	125 x 114 x 37.5 mm (4.92 x 4.49 x 1.48 in)
Weight	450 g (0.99 lbs)

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it