

NL2MPXX

2 POLE CHASSIS SPEAKON CONNECTOR, BLACK D-SIZE FLANGE, 3/16" FLAT TABS - MALE

This connector is fully compliant to the device standard IEC 62368-1, due to its component certification according to IEC 61984.

NL2MPXX

2 pole chassis connector, black D-size flange, countersunk thru holes, 3/16" flat tabs. Does not intermate with the 4-pole cable connector.

The speakON panel mount connectors are the standard chassis connectors for loudspeaker / amplifier interconnections. They feature a unique metal locking system, making contact only once fully locked. The speakON receptacles are robust, versatile and easy to terminate.

NL2MPXX

2 POLE CHASSIS SPEAKON CONNECTOR, BLACK D-SIZE FLANGE, 3/16" FLAT TABS - MALE

PRODUCT DETAILS

KEY FEATURES

IEC 61984 certified > IEC 62368-1 compliant

Glass reinforced V-0 materials make it extremely robust and dependable

Precise keyway for secure mating

Accurate twist lock latching system

Metal insert in locking area

SPECIFICATIONS

Gender	male
Contact resistance	? 2 m?
Dielectric strength	2.8 kVac
Insulation resistance	>0.1 G? (after dampheat)
Rated current per contact	24 A rms continuous (audio rating significantly higher, depending on signal)
Rated voltage	250 V ac
Attention	speakON is NOT to be used as an AC mains or power supply connector!
Lifetime	> 5000 mating cycles
Termination	3/16" flat tabs (e.g. NLFASTON)
Locking device	Quick Lock
Chassis shape	D
Layout	standard hole position, thru holes

NL2MPXX

2 POLE CHASSIS SPEAKON CONNECTOR, BLACK D-SIZE FLANGE, 3/16" FLAT TABS - MALE

Contact plating	Ag	
Locking element	Stainless Steel	
Shell	Polyamide (PA 6.6)	
Contacts	Copper Alloy	
Flammability	UL94 V-0	
Temperature range	-30 °C to +80 °C	