CL-XLR3DMX-10

DMX CABLE XLR 3 PIN (10 MT)

CENTOLIGHT DMX cables are designed for professional AVL (Audio, Video, and Lighting) applications, providing reliable signal transmission for lighting control systems. Manufactured with high-quality materials, these cables ensure low interference, maximum signal integrity, and durability.

They are ideal for use in stage productions, concerts, theaters, and fixed installations where a stable and precise DMX signal is crucial.

CL-XLR3DMX-10

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

CL-XLR3DMX-10

DMX CABLE XLR 3 PIN (10 MT)

PRODUCT DETAILS

KEY FEATURES

- Professional DMX cable built with the best materials
- O.F.C construction
- High quality jacket PVC ensures unmatched durability
- Flexibile, easy winding
- Applications: productions, concerts, theaters, and fixed installations
- Lenght: 10 mt

SPECIFICATIONS

Connector	XLR 3 PIN
PVC diameter	6.5 mm
No. of inner conductors	2x0.34 mm²
Copper strand per conductor	7x0.25 mm
Conductor insulation	PE 1.70 mm
Shielding	copper spiral shielding with 80 x 0.10 mm + AL/PT-foil + PE filter
Shielding factor	100%
Capac. cond./cond. per 1 m	52 pF
Capac. cond./shield. per 1 m	105 pF
Cond. resistance per 1 m	55 m?
Shield. resistance per 1 m	27 m?

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it