

GO-SOUND 15AM 880 WATT 15" POLYPROPYLENE ACTIVE SPEAKER WITH MP3/ BLUETOOTH™ PLAYER

Go-Sound series is built with the user in mind. As result of years of experience gathered by Soundsation in portable sound systems, we designed these versatile high-quality speakers with unmatched value and performances. Built in a polypropylene cabinet, sturdy yet compact and lightweight, these active speaker are equipped with Class AB amplifiers, which guarantee reliability and outstanding performances. Mic and line inputs are included to allow the user to connect various audio sources such as microphones, mixers as well as smartphones and tablets. The "M" models feature a full functional multimedia player with Bluetooth™ and USB/SD card reader to play your favorites tunes conveniently. Go-Sound series is an incredible value and the perfect solution in many situations such as parties, presentations, schools, conference and live music, delivering great sound quality, reliability and ease of use.



GO-SOUND 15AM

880 WATT 15" POLYPROPYLENE ACTIVE SPEAKER WITH MP3/ BLUETOOTH™ PLAYER

PRODUCT DETAILS

KEY FEATURES

2-Way Active Speaker

Sturdy polypropylene enclosure yet compact and lightweight

880 Watt class AB power amplifier

15" woofer with 1.35" compression driver

Large LCD display MP3 player with USB/SD input and Bluetooth™ and to play your favourites tunes

Balanced Microphone/Line inputs XLR + ¼" Jack, line inputs Stereo RCA + XLR, line input stereo Mini jack ideal to connect smartphones and tablets

XLR line output

Mic/line switch, volume and equalizer (Hi and Low) controls

36 mm standard pole mount

2 side handles, 1 on top and wheels for convenient carrying

Speaker Dimension (WxHxD): 440 x 703 x 370 mm

Weight: 15 Kg

SPECIFICATIONS

2-Way active speaker

Woofer	15" with 2.5" voice coil
Compression driver	1.35" voice coil, 1" throat
Directivity	90° x 50°, asymmetric

GO-SOUND 15AM

880 WATT 15" POLYPROPYLENE ACTIVE SPEAKER WITH MP3/ BLUETOOTH™ PLAYER

Frequency Response [- 3dB]	55Hz - 18KHz
Frequency Response [- 10dB]	50Hz - 18KHz
Max SPL(Peak)	116dB
Sensitivity	95dB
Class AB amplifier	
Power (Peak/Rated)	880W/440W
Crossover	2.7KHz, 24dB/Oct.
EQ	High (2.5KHz, +/- 12 dB); Low (150Hz, +/- 12 dB)
USB/SD input	compatible with memory stick/sd card up to 32 GB
Media player formats	MP3 fino a 320kBs e Wav 16 bit 44.1 kHz
LEDs	Power On (Green), Clip (Red)
Power Requirement	230Vac - 50 Hz
Minimum Power Consumption	230W
Power Connector	VDE with T3.15A-250V Fuse
Speaker Dimension (WxHxD)	440 x 703 x 370 mm
Weight	15 Kg