

XY-215S **DUAL 15-INCH QUASI-BANDPASS SUBWOOFER**

A versatile PA/monitor speaker series that is compact in size and perfect for near-field monitoring – yet can deliver highquality sound to the corners of the room. Boasts multiple installment options for easy set up.









XY-215S

DUAL 15-INCH QUASI-BANDPASS SUBWOOFER

PRODUCT DETAILS

KEY FEATURES

A quasi-bandpass subwoofer with two 15-inch LF drivers.

High-response deep bass as low as 42 Hz is delivered to reproduce a tight and punchy kick.

Two drivers efficiently generate air vibration to boost radiation efficiency.

Requires an active crossover to set the necessary frequency range (presets can be provided from Pioneer for combinations using the Pioneer XY-152, XY-122, XY-101 and XY-81).

NL4 INPUT and LINK OUT connections as standard.

Robust enclosure made from premium multi-laminate birch plywood

SPECIFICATIONS

Enclosure Type	Dual driver, quasi-bandpass subwoofer
Frequency Response	42 Hz to 160 Hz
Sensitivity (1 W/1 m) 102 dB (half space)	

Impedance 4 ohm

Nominal Power Handling 800 W RMS, 1600 W Program

Driver Configuration 2 x 15 inch (380 mm) LF cone drivers

Connectors 2 x Neutrik SpeakON™ NL4

Dimensions (WxHxD) 831 x 526 x 700 mm (32.7 x 20.7 x 27.6-inch)

Weight 71 kg (156.6 lbs)

Rigging and Hardware 4 x flush handles,2 x M20 polemount sockets for mid/high enclosures,8 x rubber feet

(bottom and left) and 4 xmating recesses (top),16 x M8 holes with pre-inserted bolts for

4 x castors on rear

Grille Hex punched steel





XY-215S

DUAL 15-INCH QUASI-BANDPASS SUBWOOFER

Enclosure 18 mm (0.7-inch) birch plywood

Finish Impact-resistant, Black semi-matt textured

Suggested/Reccomended Power

K3DSP / K2DSP

Amplifier

Accessories 2 x polemount socket cover(-W model only)

