

## CLARITY A6-W BI-AMPLIFIED 2-WAY WHITE STUDIO MONITOR WITH 6,5" WOOFER

The CLARITY A6-W studio monitor is part of the new CLARITY Studio Monitor series and is an optimal solution for both home recording and the Studio. The technological implementation makes these Monitors ideal for high-level listening thanks to the linear frequency response and the possibility of adjustment for high and low frequencies. The wide choice of inputs positioned on the rear panel (XLR, TRS, RCA) guarantees ease of use. The modern and refined design and the satin white finish make this studio monitor elegant and suitable for many environments.



# CLARITY A6-W BI-AMPLIFIED 2-WAY WHITE STUDIO MONITOR WITH 6,5" WOOFER

## PRODUCT DETAILS

### KEY FEATURES

Biamp two ways active speaker

60W RMS output power Woofer

30W RMS output power Tweeter

45Hz - 22KHz Frequency Response at -10dB

6.5" Woofer

1.0" Tweeter Silk Dome

Attenuation of High Frequencies (-2/-1/0/+1dB above 2KHz)

Attenuation of Low Frequencies (-2/-1/0/+2dB below 100Hz)

Balanced 1/4 "TS / XLR and unbalanced RCA inputs

Satin White finish

Rugged MDF Case

### SPECIFICATIONS

<b>Speaker Type</b>	Biamp two ways active speaker
<b>Mains Power</b>	220-240V~/50-60Hz
<b>Fuse</b>	T5AL250V
<b>Frequency response (-10dB)</b>	45Hz- 22KHz
<b>Woofer</b>	6,5" (Paper Cone)
<b>Tweeter</b>	1,0" (Silk Dome)

## CLARITY A6-W BI-AMPLIFIED 2-WAY WHITE STUDIO MONITOR WITH 6,5" WOOFER

<b>Crossover</b>	2.5KHz
<b>Woofer Output Power</b>	60W RMS
<b>Tweeter Output Power</b>	30W RMS
<b>SPL (1m axial direction)</b>	111dB
<b>Audio Input Connections</b>	Balanced type 1/4" XLR interface, unbalanced RCA
<b>High Frequency Adjustment</b>	-2/-1/0/+1dB above 2KHz
<b>Low Frequency Adjustment</b>	-2/-1/0/+2dB below 100Hz
<b>Cabinet Material</b>	MDF
<b>Dimensions(WxDxH)</b>	224 x 253 x 350 mm
<b>Weight</b>	7,4Kg
<b>Packing Dimensions(WxDxH)</b>	265 x 325 x 410 mm
<b>Packing Weight</b>	6,5Kg