

LIDO-420 WPW

## 4" WATERPROOF 2-WAY PASSIVE WALL-MOUNT SPEAKER PAIR, WHITE

LIDO series is specifically designed for both indoor and outdoor applications in projects with constant voltage or low impedance systems. Thanks to the IP65 protection rating, to the PP woofers, to the UV-resistant PP cabinets, to the stainless-steel metal parts, and to the aluminum grille, these speakers do not fear the rigors of exposure to atmospheric agents.

The high excursion custom transducers guarantee a clear and defined sound, always providing a higher audio quality even at high sound pressures. The power-tap selector allows you to select 3 powers and adapt the speaker to 100V or low impedance systems. The C-bracket allows you to adjust the horizontal (+55°/-55°) and vertical position (+20°/-20°).



LIDO-420 WPW

# 4" WATERPROOF 2-WAY PASSIVE WALL-MOUNT SPEAKER PAIR, WHITE

## HIGHLIGHTS



### WEATHER-RESISTANT TRANSDUCERS

Woofer and Dome Tweeter are made of water-resistant materials to allow use in outdoor places exposed to rain and moisture. Material type and thicknesses of the external parts have been designed to maintain a good frequency linearity and dynamic response.

### DETAILS DESIGNED FOR A LONG-LIFE CYCLE

All materials are designed to increase speaker life cycle, even when installed in outdoor environments without protections. The cabinet and rubber covers are made of UV-resistant plastic material. The front grille is in aluminum with treatment against atmospheric agents, and the fixing screws are in stainless steel.



# LIDO-420 WPW

## 4" WATERPROOF 2-WAY PASSIVE WALL-MOUNT SPEAKER PAIR, WHITE

### PRODUCT DETAILS

#### KEY FEATURES

- 2-Way Passive system with 20W RMS Power
- IP65 Protection Rating for Outdoor/Indoor Applications
- UV-Resistant PP Housing
- Built-in 100V Line Transformer
- Power Tap Selector for 100V or low-impedance systems
- Horizontal and Vertical adjustable C-Bracket
- Paintable Housing and Grille

#### SPECIFICATIONS

Speaker Type	2-Way Passive
IP Rating	IP65
RMS Power (@ 8ohm)	20W
70V Powers	2.5W – 5W – 10W
100V Powers	5W – 10W – 20W
Frequency Response (-10dB)	90Hz-18kHz
Sensitivity (1w@1m)	88dB
Impedance	8ohm
Woofer	4" (103mm), PP cone
Tweeter	0.5" (13mm), Mylar dome

LIDO-420 WPW

## 4" WATERPROOF 2-WAY PASSIVE WALL-MOUNT SPEAKER PAIR, WHITE

<b>Housing</b>	UV-Resistant PP, paintable	
<b>Bracket</b>	C-Bracket with Pan/Tilt adjustable angle and stainless steel screws	
<b>Grille</b>	Perforated aluminum, powder coated paint, acoustic transparent foam inside, paintable	
<b>Color</b>	White	
<b>Product Size (WxDxH)</b>	138 x 120 x 220mm	
<b>Speaker Weight (single unit)</b>	1,432 kg	
<b>Packing Size (WxDxH) (pair)</b>	335 x 190 x 260 mm	
<b>Packing Weight (pair)</b>	3,6 kg	