

XY-218S HIGH-POWER SUBWOOFER WITH TWO 18-INCH, LOW-FREQUENCY DRIVER.

A versatile PA/monitor speaker series that is compact in size and perfect for near-field monitoring – yet can deliver highquality sound to the corners of the room. Boasts multiple installment options for easy set up.









FRENEXPORT

Via Enzo Ferrari 10 62017 Porto Recanati (MC), Italy info@frenexport.it



XY-218S HIGH-POWER SUBWOOFER WITH TWO 18-INCH, LOW-FREQUENCY DRIVER.

PRODUCT DETAILS

KEY FEATURES

High-power subwoofer with two 18-inch, low-frequency drivers.

Capable of reproducing deep bass as low as 32 Hz without distortion.

Strong pillars installed in the cabinet ensure rigidity against the most powerful bass.

Requires an active crossover to set the necessary frequency range

NL4 INPUT and LINK OUT connections as standard.

Pole mount for quick set-up with other Pioneer products.

Robust enclosure made from premium multi-laminate birch plywood.

SPECIFICATIONS

Enclosure Type	two drivers, reflex-loaded subwoofer
Frequency Response	32 Hz to 150 Hz
Sensitivity (1 W/1 m)	102 dB (half space)
Nominal Impedance	4 Ohm
Power Handling	1600 W RMS, 3200 W Program
Maximum SPL	134 dB cont., 140 dB peak (half space)
Driver Configuration	2 x 18 inch (460 mm) neodymium LF cone driver
Connectors	2 × Neutrik SpeakON™ NL4
Dimensions (W×H×D)	1164 × 558 × 745 mm (23.2 × 25.3 × 25.6 inch)
Weight	93 kg (205 lbs)

FRENEXPORT

Via Enzo Ferrari 10 62017 Porto Recanati (MC), Italy info@frenexport.it



XY-218S HIGH-POWER SUBWOOFER WITH TWO 18-INCH, LOW-FREQUENCY DRIVER.

Rigging and Hardware	8 × flush handles (4 left/4 right),4 × rubber feet (bottom) and 4 ×mating recesses (top), 16 x threaded points M8 for 4 castors
Grille	Hex punched steel
Enclosure	18 mm (0.7 inch) birch plywood
Finish	Impact-resistant, Black semi-matt textured
Suggested Power Amplifier	K10DSP
Accessories	polemount socket cover(-W model only)

FRENEXPORT

Via Enzo Ferrari 10 62017 Porto Recanati (MC), Italy info@frenexport.it